



Dose Rate Meter

GRAETZ GammaTwin

- small and handy, PTB-approved ¹⁾ dose rate meter for the measurement of gamma radiation and X-rays for ambient dose rate equivalent $\dot{H}^*(10)$ and ambient dose equivalent $H^*(10)$ (local dose) ²⁾
- detector: energy compensated Geiger-Müller-tube
- large, digital indication of measured values on LC-display (backlit)
- selectable simultaneous or separate indication of dose and dose rate, additionally analog indication of dose rate (logarithmic bargraph)
- 4 preset dose and dose rate alarm thresholds; upon request GRAETZ changes the standard alarm thresholds according to customer requirements
- switchable acoustic single-pulse indication
- automatic and continuous storage of the dose into a non-volatile memory
- storage of the dose and of set parameters even at battery change
- permanent self test
- designed for rough use, housing made of aluminium, protection class IP54 (splash proof)
- menu-driven user navigation
- supplied with a robust nylon bag

¹⁾ Physikalisch-Technische Bundesanstalt, Braunschweig

²⁾ For detecting the personal dose a measuring instrument with the measurand $H_p(10)$ is required.



Technical Data


Dose rate indication range:	0 nSv/h – 70 mSv/h
Dose rate measuring range:	0.5 µSv/h – 70 mSv/h
Dose indication range:	0 nSv – 1.0 Sv
Dose measuring range:	0.5 µSv – 1.0 Sv
Energy range:	45 keV – 1.3 MeV
Dose rate alarm thresholds:	7.5 µSv/h, 25 µSv/h, 40 µSv/h, 300 µSv/h
Dose alarm thresholds:	200 µSv, 500 µSv, 1000 µSv, 2000 µSv
Temperature range:	-20 °C up to +60 °C
Power supply:	2 batteries 1.5 V (type AAA)
Acoustic alarm:	80 dB(A) measured in 30 cm distance
PTB-Approval No.:	23.51 / 10.02
Dimensions:	(26 x 66 x 103) mm
Weight:	190 g (with batteries)

Available special version:

GammaTwin S with connection facility for external probes (such as the NaI-scintillation probe 2002 for high-sensitive β - and γ -measurement or the large-area probe ABG170 for the detection of contaminations)

09/2013

Subject to
technical change



GRAETZ Strahlungsmeßtechnik GmbH

Westiger Str. 172 • 58762 Altena / Germany
P.O. Box 81 00 • 58754 Altena / Germany
Phone: +49 2352 7007-0 • Fax: +49 2352 7007-10
E-Mail: info@graetz.com • Website: www.graetz.com