

XRIS

Dereo PS 2530

Battery powered Portable X-ray DDA for Smart NDT inspections

APPLICATIONS

- ▶ Portable digital system for indoor and outdoor x-ray jobs
- Quality control of aerospace structures, shipyards, pipes, power lines, buildings, railway, windmills, ammunitions, ...
- ▶ Periodic maintenance control
- ▶ Weldings, castings, corrosion under insulation, composite materials,...
- ▶ Historical assets (in Museums, laboratories, universities,...)



KEY FEATURES

Very portable X-ray pictures anywhere.

Battery powered.

Large area Active area of 24 x 30 cm.

Quick set-up X-ray pictures at anytime.

Digital Instant results.

sensitivity

Very easy set-up and use, thanks to the automatic real-time filter magnifier, and to the wide contrast latitude of digital

technologies.

Very user-friendly **Maestro** software.

Post-processing.

TIFF & JPG format.

Easy archiving & reporting.

No more consumables (films and chemicals) & dark room

needed.

Image quality High resolution (from 120 down to 68 μ m depending on binning

mode) and high contrast (16 bit).

High Ability to X-ray a large range of different objects and materials,

from light materials such as paper, up to several mm Fe.

Real-time Real-time X-ray pictures for urgent image acquisition and

analysis.

Robust Real 2D panel. There are no mirror, neither fragile moving parts

inside the detector such as engine and belt.







Dereo PS DDA SPECIFICATIONS




MODEL	TECHNOLOGY	ACTIVE AREA (cm)	PIXEL SIZE (μm)	GREY LEVEL (bit)	EXTERNAL DIMENSIONS) (mm)	WEIGHT (kg)
Dereo PS 2530	DRZ-Std / Csl Camera	24 x 30	68 or 120	16	256 x 410 x 77	7,2

Maestro SOFTWARE

- ▶ Software interfaces developed by and with field users
- ▶ Maestro Touch for touchpads and Maestro for laptops
- Very intuitive software interfaces. Access to all key tools of Maestro Touch with your thumbs and with one click mouse on Maestro
- ➤ Zoom in / out, screen adjustment, rotation, horizontal and vertical flip, cropping, ...
- ▶ Access to the LUT (look-up-table)
- ▶ Black and white reversal
- Annotations
- ▶ Real time magnifier
- ▶ Real time filters (ACUITY, Defect, Contrast, Edge, Noise reduction, ...)
- Smart measurement tools
- NDT Tools for normative inspections
- ▶ Bad pixels map
- ▶ DICONDE
- Compliant with all major NDT standards (ISO 17636, ASTM-E 2698, E2736, E2737, E2597, Safran PR5250, Airbus AITM 6-7007 and Boeing BSS-7044
- ▶ Wall thickness measurement
- Control of many X-ray generator brands and models
- Any language available upon request
- > X-RIS is open to discuss the development of new software tools





Dereo PS ACCESSORIES

- ▶ GemX constant potential X-ray generator
- Wireless modules
- Battery-powered
- ▶ IP66 Carrying case
- ▶ Backpack



www.xris.eu

